



Stock Price List

\$50 Minimum Order

Panel Saws / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Millimeters)	Number of Teeth	Thickness		Bore (Millimeters)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	(Millimeters)					1-5	6-20	21-49	50+
125 - 24 - 28 - 2	125	24	0.110	2.8	45.0	8°	.327 x .055	NO SLOTS/GIBEN	15.69	14.38	13.73	13.08
160 - 36 - 32 - 5	160	36	0.126	3.2	55.0	8°	.244 x .063	No Slots, PH3/7/66, Var.Mfg.	28.14	25.79	24.62	23.45
180 - 36 - 35 - 5	180	36	0.138	3.5	45.0	8°	.315 x .063	No Slots, Holzma	26.47	24.25	23.15	22.06
200 - 36 - 32 - 10	200	36	0.126	3.2	20.0	8°	.315 x .063	3/CU, Var.Mfg.	23.94	21.94	20.94	19.95
200 - 36 - 32 - 11	200	36	0.126	3.2	65.0	8°	.315 x .063	3/CU,PH.2/9/100, Var.Mfg.	25.47	23.35	22.30	21.23
200 - 36 - 35 - 17	200	36	0.138	3.5	45.0	8°	.331 x .055	3/CU, Holzma	30.33	27.80	26.54	25.28
200 - 36 - 40 - 5	200	36	0.157	4.0	45.0	8°	.244 x .063	3/CU,PH.2/14/65, Var.Mfg.	54.80	50.23	47.94	45.67
220 - 64 - 20 - 1	220	64	0.079	2.0	30.0	10°	.236 x .055	2/PH, Var.Mfg.	21.37	19.60	18.70	17.81
300 - 72 - 22 - 36	300	72	0.087	2.2	30.0	10°	.327 x .055	4/CU,PH 2/7/42&2/10/60Var.Mfg.	31.57	28.93	27.61	26.30
300 - 96 - 22 - 28	300	96	0.087	2.2	30.0	10°	.236 x .055	4/CU, Var.Mfg.	32.45	29.74	28.39	27.04
350 - 72 - 30 - 19	350	72	0.118	3.0	30.0	10°	.236 x .063	4/CU,PH.2/10/60, Var.Mfg.	43.93	40.27	38.44	36.60
380 - 72 - 35 - 10	380	72	0.138	3.5	60.0	10°	.244 x .063	4/CU,PH.2/10/80, Holzma	60.75	55.68	53.16	50.62
380 - 72 - 35 - 12	380	72	0.138	3.5	60.0	15	.244 x .063	4/CU,PH.2/14/100	60.75	55.68	53.16	50.62
400 - 60 - 28 - 3	400	60	0.110	2.8	75.0	10°	.323 x .055	6/CU+CS, GIBEN	46.60	42.72	40.77	38.84
400 - 72 - 32 - 22	400	72	0.126	3.2	30.0	15°	.244 x .063	4/CU, Var.Mfg.	51.46	47.18	45.03	42.88
400 - 72 - 32 - 23	400	72	0.126	3.2	75.0	15°	.244 x .063	4/CU,PH.4/15/105, Var.Mfg.	52.82	48.42	46.22	44.01
420 - 72 - 35 - 4	420	72	0.138	3.5	60.0	15°	.244 x .063	4/CU, Holzma	72.55	66.49	63.48	60.46
450 - 72 - 35 - 12	450	72	0.138	3.5	60.0	15°	.272 x .063	4/CU,PH.2/14/125, Holzma	75.64	69.33	66.18	63.03
500 - 72 - 35 - 9	500	72	0.138	3.5	60.0	15°	.280 x .063	6/CU,PH.2/11/115, Holzma	83.26	76.33	72.86	69.39
600 - 60 - 40 - 6	600	60	0.157	4.0	60.0	15°	.280 x .055	6/CU,PH.2/11/115 & 2/19/120,Var.Mfg.	119.70	109.73	104.74	99.76