



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
102 - 12 - 22 - 1	4	12	0.087	14	3/4	15°	.236 x .063	NO SLOTS	11.53	10.58	10.10	9.61
102 - 12 - 24 - 2	4	12	0.094	13	5/8	15°	.236 x .063	NO SLOTS	11.71	10.73	10.24	9.75
102 - 18 - 22 - 1	4	18	0.087	14	3/4	0°	.236 x .063	NO SLOTS	11.89	10.90	10.41	9.91
102 - 30 - 22 - 1	4	30	0.087	14	3/4	0°	.236 x .063	NO SLOTS	12.31	11.28	10.76	10.25
115 - 24 - 22 - 2	4-1/2	24	0.087	14	3/8	10°	.236 x .055	NO SLOTS	12.77	11.70	11.17	10.64
115 - 40 - 18 - 1	4-1/2	40	0.071	15	3/8	5°	.189 x .051	NO SLOTS	12.40	11.37	10.86	10.34
150 - 16 - 22 - 1	6	16	0.087	14	5/8	15°	.236 x .063		10.96	10.06	9.60	9.14
150 - 30 - 22 - 1	6	30	0.087	14	5/8	10°	.236 x .063		11.75	10.78	10.29	9.80
150 - 40 - 22 - 1	6	40	0.087	14	5/8	5°	.236 x .063		12.44	11.40	10.88	10.36
165 - 24 - 18 - 1	6-1/2	24	0.071	15	5/8 SKIL	15°	.252 x .063	SKIL	13.97	12.80	12.22	11.64
165 - 40 - 18 - 1	6-1/2	40	0.071	15	5/8 SKIL	10°	.236 x .063	SKIL	14.90	13.66	13.03	12.41
180 - 40 - 22 - 1	7	40	0.087	14	5/8	10°	.236 x .063		14.08	12.90	12.33	11.74
185 - 24 - 18 - 1	7-1/4	24	0.071	15	5/8 SKIL	15°	.252 x .063	SKIL	13.03	11.94	11.40	10.86
185 - 40 - 18 - 1	7-1/4	40	0.071	15	5/8 SKIL	10°	.236 x .063	SKIL	13.82	12.66	12.10	11.52
185 - 60 - 18 - 1	7-1/4	60	0.071	15	5/8 SKIL	5°	.236 x .063	SKIL	15.02	13.78	13.14	12.52
205 - 24 - 22 - 1	8	24	0.087	14	5/8	15°	.236 x .063		12.74	11.67	11.14	10.61
205 - 24 - 24 - 1	8	24	0.094	13	5/8	15°	.236 x .063		14.48	13.27	12.66	12.06
205 - 40 - 22 - 2	8	40	0.087	14	5/8	10°	.236 x .063		13.59	12.47	11.89	11.33
205 - 40 - 24 - 5	8	40	0.094	13	5/8	10°	.236 x .063		15.27	14.00	13.36	12.73
205 - 40 - 34 - 2	8	40	0.134	10	5/8	10°	.236 x .063		20.01	18.34	17.50	16.68
205 - 48 - 22 - 1	8	48	0.087	14	5/8	10°	.236 x .063		15.15	13.89	13.25	12.62
205 - 60 - 22 - 1	8	60	0.087	14	5/8	5°	.236 x .063		14.61	13.39	12.78	12.17
205 - 60 - 24 - 1	8	60	0.094	13	5/8	5°	.236 x .063		17.05	15.64	14.93	14.21
205 - 60 - 28 - 1	8	60	0.110	12	5/8	5°	.236 x .063		20.02	18.35	17.53	16.69
205 - 60 - 34 - 1	8	60	0.134	10	5/8	5°	.236 x .063		24.27	22.24	21.24	20.23
230 - 24 - 22 - 1	9	24	0.087	14	5/8	15°	.236 x .063		15.77	14.46	13.79	13.13
230 - 40 - 22 - 2	9	40	0.087	14	5/8	15°	.236 x .063		17.00	15.57	14.88	14.17
230 - 60 - 22 - 2	9	60	0.087	14	5/8	5°	.236 x .063		18.42	16.89	16.13	15.36
230 - 72 - 22 - 1	9	72	0.087	14	5/8	5°	.236 x .063	4 CU	22.24	20.39	19.46	18.54
255 - 24 - 22 - 1	10	24	0.087	14	5/8	20°	.252 x .079		16.18	14.84	14.17	13.49
255 - 24 - 24 - 1	10	24	0.094	13	5/8	20°	.252 x .079		17.00	15.58	14.88	14.17
255 - 24 - 28 - 1	10	24	0.110	12	5/8	20°	.236 x .079		22.07	20.22	19.31	18.39
255 - 30 - 22 - 1	10	30	0.087	14	5/8	20°	.252 x .079		19.40	17.78	16.99	16.17
255 - 30 - 24 - 1	10	30	0.094	13	5/8	20°	.252 x .079		20.23	18.54	17.70	16.86
255 - 40 - 22 - 2	10	40	0.087	14	5/8	15°	.236 x .063	4 CU	20.06	18.38	17.55	16.71



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
255 - 40 - 22 - 3	10	40	0.087	14	5/8	15°	.236 x .063		18.68	17.12	16.34	15.57
255 - 40 - 24 - 2	10	40	0.094	13	5/8	15°	.236 x .063		19.65	18.01	17.20	16.38
255 - 40 - 28 - 1	10	40	0.110	12	5/8	15°	.236 x .063		24.85	22.78	21.75	20.71
255 - 40 - 34 - 1	10	40	0.134	10	5/8	15°	.236 x .063		27.05	24.79	23.68	22.54
255 - 48 - 22 - 1	10	48	0.087	14	5/8	10°	.236 x .063		20.36	18.65	17.80	16.95
255 - 48 - 24 - 1	10	48	0.094	13	5/8	10°	.236 x .063	3 CU	22.46	20.59	19.64	18.72
255 - 60 - 22 - 1	10	60	0.087	14	5/8	10°	.236 x .063		18.11	16.61	15.85	15.10
255 - 60 - 22 - 2	10	60	0.087	14	5/8	10°	.236 x .063	3 CU	20.44	18.73	17.87	17.02
255 - 60 - 24 - 1	10	60	0.094	13	5/8	10°	.236 x .063		20.54	18.83	17.97	17.11
255 - 60 - 24 - 2	10	60	0.094	13	5/8	5°	.236 x .063	4 CU	21.10	19.35	18.47	17.60
255 - 60 - 28 - 2	10	60	0.110	12	5/8	5°	.236 x .063	4 CU	23.99	22.00	21.00	20.00
255 - 60 - 30 - 1	10	60	0.118	11	5/8	10°	.236 x .063		25.08	22.99	21.94	20.90
255 - 60 - 34 - 1	10	60	0.134	10	5/8	10°	.236 x .063		27.75	25.44	24.28	23.13
255 - 80 - 22 - 2	10	80	0.087	14	5/8	5°	.236 x .063	4 CU	20.42	18.72	17.86	17.01
255 - 80 - 24 - 1	10	80	0.094	13	5/8	5°	.236 x .063	4 CU	23.99	22.00	20.99	20.00
255 - 80 - 28 - 2	10	80	0.110	12	5/8	10°	.236 x .063	4 CU	26.94	24.71	23.58	22.46
255 - 80 - 30 - 1	10	80	0.118	11	5/8	5°	.236 x .063		26.58	24.37	23.25	22.15
305 - 12 - 28 - 1	12	12	0.110	12	1	25°	.252 x .087	NO SLOTS	25.52	23.39	22.32	21.26
305 - 24 - 22 - 1	12	24	0.087	14	1	20°	.252 x .063	3 CU	23.83	21.83	20.84	19.85
305 - 24 - 24 - 1	12	24	0.094	13	1	20°	.252 x .079	3 CU	25.23	23.14	22.08	21.03
305 - 24 - 28 - 1	12	24	0.110	12	1	20°	.252 x .079	3 CU	26.39	24.20	23.10	22.00
305 - 24 - 28 - 135	12	24	0.110	12	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	27.26	25.01	23.86	22.71
305 - 24 - 30 - 1	12	24	0.118	11	1	20°	.252 x .079	3 CU	28.26	25.90	24.73	23.55
305 - 24 - 34 - 1	12	24	0.134	10	1	20°	.252 x .079	3 CU	30.45	27.92	26.65	25.38
305 - 30 - 22 - 1	12	30	0.087	14	1	20°	.252 x .079	3 CU	23.93	21.94	20.94	19.94
305 - 30 - 24 - 1	12	30	0.094	13	1	20°	.252 x .079	3 CU	25.19	23.09	22.03	20.99
305 - 30 - 28 - 1	12	30	0.110	12	1	20°	.252 x .079	3 CU	26.92	24.67	23.55	22.44
305 - 30 - 30 - 1	12	30	0.118	11	1	20°	.252 x .079	3 CU	28.51	26.14	24.96	23.76
305 - 30 - 34 - 1	12	30	0.134	10	1	20°	.252 x .079	3 CU	31.33	28.72	27.42	26.12
305 - 36 - 24 - 1	12	36	0.094	13	1	20°	.252 x .079	3 CU	26.53	24.32	23.22	22.11
305 - 36 - 24 - 107	12	36	0.094	13	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	26.39	24.27	23.17	22.08
305 - 36 - 28 - 1	12	36	0.110	12	1	20°	.252 x .079	3 CU	27.29	25.01	23.87	22.74
305 - 36 - 28 - 172	12	36	0.110	12	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	27.26	25.01	23.86	22.71
305 - 36 - 30 - 1	12	36	0.118	11	1	20°	.252 x .079	3 CU	28.96	26.54	25.33	24.13
305 - 36 - 34 - 1	12	36	0.134	10	1	20°	.252 x .079	3 CU	32.18	29.50	28.15	26.82
305 - 40 - 24 - 2	12	40	0.094	13	1	15°	.236 x .063	4 CU	25.47	23.36	22.29	21.23



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
305 - 40 - 28 - 1	12	40	0.110	12	1	15°	.236 x .063	4 CU	28.00	25.68	24.51	23.35
305 - 40 - 30 - 1	12	40	0.118	11	1	15°	.236 x .063	4 CU	28.27	25.90	24.74	23.55
305 - 40 - 34 - 1	12	40	0.134	10	1	15°	.236 x .063	4 CU	33.30	30.54	29.15	27.76
305 - 48 - 24 - 1	12	48	0.094	13	1	15°	.236 x .063	4 CU	26.35	24.14	23.05	21.95
305 - 60 - 24 - 1	12	60	0.094	13	1	10°	.236 x .063	4 CU	26.43	24.23	23.14	22.02
305 - 60 - 24 - 2	12	60	0.094	13	5/8	10°	.236 x .063	4 CU	28.34	25.98	24.79	23.61
305 - 60 - 28 - 2	12	60	0.110	12	1	10°	.236 x .063	4 CU	29.82	27.32	26.08	24.84
305 - 60 - 30 - 1	12	60	0.118	11	1	10°	.236 x .063	4 CU	32.50	29.79	28.44	27.08
305 - 60 - 34 - 1	12	60	0.134	10	1	10°	.236 x .063	4 CU	35.09	32.17	30.71	29.23
305 - 72 - 24 - 1	12	72	0.094	13	1	10°	.236 x .063	4 CU	27.39	25.10	23.97	22.83
305 - 72 - 30 - 1	12	72	0.118	11	1	10°	.236 x .063	4 CU	33.50	30.71	29.30	27.91
305 - 72 - 34 - 1	12	72	0.134	10	1	10°	.236 x .063	4 CU	37.70	34.56	32.99	31.42
305 - 80 - 22 - 1	12	80	0.087	14	1	5°	.236 x .063	4 CU	26.86	24.62	23.51	22.38
305 - 80 - 24 - 1	12	80	0.094	13	5/8	5°	.236 x .063	4 CU	27.97	25.63	24.47	23.31
305 - 80 - 24 - 2	12	80	0.094	13	1	5°	.236 x .063	4 CU	27.03	24.77	23.66	22.52
305 - 80 - 28 - 1	12	80	0.110	12	1	5°	.236 x .063	4 CU	32.27	29.58	28.23	26.89
305 - 80 - 30 - 1	12	80	0.118	11	1	5°	.236 x .063	4 CU	33.72	30.90	29.50	28.09
305 - 80 - 34 - 1	12	80	0.134	10	1	5°	.236 x .063	4 CU	37.54	34.41	32.84	31.28
305 - 100 - 22 - 1	12	100	0.087	14	1	5°	.236 x .063	4 CU	28.80	26.39	25.20	23.99
305 - 100 - 24 - 1	12	100	0.094	13	1	5°	.236 x .063	4 CU	27.54	25.25	24.09	22.95
305 - 100 - 28 - 1	12	100	0.110	12	1	5°	.236 x .063	4 CU	33.09	30.34	28.96	27.58
305 - 100 - 30 - 1	12	100	0.118	11	1	5°	.236 x .063	4 CU	34.75	31.84	30.41	28.96
305 - 100 - 34 - 1	12	100	0.134	10	1	5°	.236 x .063	4 CU	38.47	35.27	33.65	32.05
355 - 30 - 30 - 1	14	30	0.118	11	1	20°	.252 x .079	4 CU	36.75	33.70	32.15	30.62
355 - 30 - 34 - 1	14	30	0.134	10	1	20°	.252 x .079	4 CU	40.91	37.49	35.79	34.09
355 - 36 - 25 - 1	14	36	0.098	13	1	20°	.252 x .079	4 CU	33.38	30.60	29.21	27.82
355 - 36 - 30 - 1	14	36	0.118	11	1	20°	.252 x .079	4 CU	36.81	33.74	32.21	30.68
355 - 36 - 34 - 1	14	36	0.134	10	1	20°	.252 x .079	4 CU	41.79	38.31	36.57	34.82
355 - 40 - 28 - 1	14	40	0.110	12	1	15°	.236 x .063	4 CU	35.43	32.48	30.99	29.52
355 - 40 - 30 - 1	14	40	0.118	11	1	15°	.236 x .063	4 CU	37.20	34.10	32.55	30.99
355 - 40 - 34 - 10	14	40	0.134	10	1	15°	.236 x .063	4 CU	41.99	38.48	36.73	34.98
355 - 40 - 34 - 2	14	40	0.134	10	2	15°	.236 x .063	4 CU/PH - Diehl	43.71	40.07	38.25	36.42
355 - 60 - 28 - 1	14	60	0.110	12	1	10°	.236 x .063	4 CU	36.79	33.73	32.20	30.66
355 - 60 - 30 - 1	14	60	0.118	11	1	10°	.236 x .063	4 CU	39.18	35.90	34.28	32.65
355 - 60 - 34 - 1	14	60	0.134	10	1	10°	.236 x .063	4 CU	43.62	39.97	38.17	36.35



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
355 - 72 - 28 - 1	14	72	0.110	12	1	10°	.236 x .063	4 CU	38.39	35.19	33.59	31.99
355 - 72 - 30 - 1	14	72	0.118	11	1	10°	.236 x .063	4 CU	40.30	36.94	35.26	33.58
355 - 72 - 34 - 1	14	72	0.134	10	1	10°	.236 x .063	4 CU	44.88	41.15	39.27	37.41
355 - 80 - 25 - 1	14	80	0.098	13	1	10°	.236 x .063	4 CU	37.61	34.48	32.90	31.34
355 - 80 - 28 - 1	14	80	0.110	12	1	10°	.236 x .063	4 CU	38.71	35.49	33.88	32.27
355 - 80 - 30 - 1	14	80	0.118	11	1	10°	.236 x .063	4 CU	40.32	36.96	35.29	33.60
355 - 80 - 34 - 1	14	80	0.134	10	1	10°	.236 x .063	4 CU	44.60	40.88	39.02	37.16
355 - 100 - 28 - 1	14	100	0.110	12	1	5°	.236 x .063	4 CU	38.67	35.45	33.83	32.22
355 - 100 - 30 - 1	14	100	0.118	11	1	5°	.236 x .063	4 CU	40.30	36.94	35.26	33.58
355 - 100 - 34 - 2	14	100	0.134	10	1	5°	.236 x .063	4 CU	46.30	42.46	40.53	38.59
355 - 120 - 30 - 2	14	120	0.118	11	1	5°	.236 x .063	4 CU	43.04	39.45	37.66	35.87
380 - 100 - 22 - 3	15	100	0.087	14	1	0°	.236 x .063	4 CU	40.50	37.12	35.44	33.75
405 - 24 - 34 - 1	16	24	0.134	10	1	20°	.252 x .079	4 CU	50.58	46.37	44.26	42.15
405 - 30 - 34 - 1	16	30	0.134	10	1	20°	.252 x .079	4 CU	50.86	46.63	44.52	42.39
405 - 36 - 30 - 1	16	36	0.118	11	1	20°	.252 x .079	4 CU	46.66	42.76	40.83	38.87
405 - 36 - 34 - 2	16	36	0.134	10	2	20°	.252 x .079	4 CU/PH - Diehl	53.03	48.60	46.40	44.18
405 - 40 - 28 - 1	16	40	0.110	12	1	15°	.236 x .063	4 CU	43.78	40.12	38.31	36.48
405 - 40 - 30 - 1	16	40	0.118	11	1	15°	.236 x .063	4 CU	43.42	39.81	38.00	36.19
405 - 40 - 34 - 1	16	40	0.134	10	1	15°	.236 x .063	4 CU	47.20	43.26	41.29	39.33
405 - 60 - 28 - 2	16	60	0.110	12	1	10°	.252 x .063	4 CU	44.55	40.84	38.99	37.12
405 - 60 - 30 - 1	16	60	0.118	11	1	10°	.252 x .063	4 CU	46.15	42.30	40.38	38.46
405 - 60 - 34 - 1	16	60	0.134	10	1	10°	.252 x .063	4 CU	49.47	45.36	43.29	41.23
405 - 80 - 30 - 2	16	80	0.118	11	1	10°	.236 x .063	4 CU	46.15	42.30	40.38	38.46
405 - 80 - 34 - 1	16	80	0.134	10	1	10°	.236 x .063	4 CU	49.86	45.71	43.63	41.56
405 - 100 - 30 - 1	16	100	0.118	11	1	5°	.236 x .063	4 CU	47.35	43.40	41.42	39.46
405 - 100 - 34 - 1	16	100	0.134	10	1	5°	.236 x .063	4 CU	50.68	46.45	44.33	42.23
405 - 120 - 30 - 1	16	120	0.118	11	1	5°	.236 x .063	4 CU	46.84	42.95	40.99	39.04
455 - 36 - 34 - 1	18	36	0.134	10	1	20°	.252 x .079	4 CU	59.27	54.31	51.85	49.38
455 - 40 - 34 - 1	18	40	0.134	10	1	15°	.236 x .063	4 CU	60.03	55.02	52.52	50.01
455 - 60 - 34 - 1	18	60	0.134	10	1	10°	.236 x .063	4 CU	62.51	57.30	54.69	52.10
455 - 60 - 38 - 1	18	60	0.150	9	1	10°	.252 x .079	4 CU	76.99	70.58	67.38	64.16
455 - 80 - 34 - 1	18	80	0.134	10	1	10°	.236 x .063	4 CU	64.65	59.27	56.57	53.88
455 - 100 - 34 - 1	18	100	0.134	10	1	10°	.236 x .063	4 CU	65.11	59.69	56.96	54.26
455 - 120 - 34 - 1	18	120	0.134	10	1	5°	.236 x .063	4 CU	66.13	60.62	57.86	55.11



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
505 - 40 - 38 - 1	20	40	0.150	9	1	20°	.252 x .079	4 CU	73.01	66.93	63.88	60.85
505 - 60 - 34 - 1	20	60	0.134	10	1	15°	.252 x .079	4 CU	69.59	63.78	60.88	57.98
505 - 60 - 34 - 3	20	60	0.134	10	1-1/4	0°	.220 x .063	4 CU	69.60	63.80	60.89	58.01
505 - 60 - 38 - 1	20	60	0.150	9	1	15°	.252 x .079	4 CU	75.76	69.45	66.30	63.14
505 - 60 - 38 - 5	20	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	75.76	69.45	66.30	63.14
505 - 80 - 34 - 1	20	80	0.134	10	1	15°	.252 x .079	4 CU	71.71	65.73	62.74	59.75
505 - 80 - 34 - 2	20	80	0.134	10	1-1/4	0°	.220 x .063	4 CU	71.71	65.73	62.74	59.75
505 - 80 - 38 - 1	20	80	0.150	9	1	15°	.252 x .079	4 CU	78.18	71.67	68.41	65.15
505 - 80 - 38 - 11	20	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	78.18	71.67	68.41	65.15
505 - 100 - 34 - 1	20	100	0.134	10	1	10°	.252 x .079	4 CU	74.98	68.72	65.61	62.48
505 - 100 - 34 - 2	20	100	0.134	10	1-1/4	0°	.220 x .063	4 CU	74.98	68.72	65.61	62.48
505 - 100 - 38 - 1	20	100	0.150	9	1	10°	.252 x .079	4 CU	81.22	74.46	71.08	67.69
505 - 100 - 38 - 4	20	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	81.22	74.46	71.08	67.69
505 - 120 - 38 - 1	20	120	0.150	9	1	10°	.252 x .079	4 CU	82.60	75.73	72.28	68.84
560 - 60 - 38 - 1	22	60	0.150	9	1	15°	.252 x .079	4 CU	89.24	81.81	78.09	74.37
560 - 60 - 38 - 10	22	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	89.24	81.81	78.09	74.37
560 - 80 - 38 - 1	22	80	0.150	9	1	15°	.252 x .079	4 CU	91.47	83.86	80.04	76.23
560 - 80 - 38 - 19	22	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	91.47	83.86	80.04	76.23
560 - 100 - 38 - 1	22	100	0.150	9	1	10°	.252 x .079	4 CU	94.97	87.06	83.10	79.14
560 - 100 - 38 - 3	22	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	94.97	87.06	83.10	79.14
560 - 120 - 38 - 1	22	120	0.150	9	1	10°	.252 x .079	5 CU	98.20	90.02	85.92	81.83
610 - 60 - 38 - 1	24	60	0.150	9	1	15°	.252 x .079	4 CU	112.01	102.68	98.01	93.35
610 - 60 - 38 - 7	24	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	112.01	102.68	98.01	93.35
610 - 80 - 38 - 1	24	80	0.150	9	1	15°	.252 x .079	4 CU	115.95	106.28	101.45	96.62
610 - 80 - 38 - 16	24	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	115.95	106.28	101.45	96.62
610 - 100 - 38 - 1	24	100	0.150	9	1	10°	.252 x .079	4 CU	120.92	110.85	105.80	100.77
610 - 100 - 38 - 3	24	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	120.92	110.85	105.80	100.77
660 - 60 - 38 - 1	26	60	0.150	9	1	10°	.252 x .079	4 CU	152.47	139.76	133.41	127.05



Stock Price List

\$50 Minimum Order

Edger Saws with Two Large Outside Slots / Saw Bodies for Carbide Tipping

Pendu

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Keyway / Pinholes	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-49	50-99	100+
255 - 10 - 21 - 2	10	10	0.083	14	2-3/8	25°	.375 x .063	3/8 Sq.	17.58	17.07	16.73	16.41
255 - 10 - 24 - 3	10	10	0.095	13	2-3/8	25°	.375 x .063	3/8 Sq.	18.32	17.80	17.45	17.09
255 - 10 - 28 - 4	10	10	0.109	12	2-3/8	25°	.375 x .063	3/8 Sq.	19.76	19.19	18.81	18.45
255 - 10 - 30 - 2	10	10	0.120	11	2-3/8	25°	.375 x .063	3/8 Sq.	20.83	20.23	19.84	19.44
305 - 12 - 21 - 1	12	12	0.083	14	2-3/8	25°	.375 x .063	3/8 Sq.	20.91	20.31	19.91	19.50
305 - 12 - 24 - 12	12	12	0.095	13	2-3/8	25°	.375 x .063	3/8 Sq.	22.11	21.49	21.07	20.64
305 - 12 - 28 - 14	12	12	0.109	12	2-3/8	25°	.375 x .063	3/8 Sq.	23.13	22.46	22.02	21.59
305 - 12 - 30 - 4	12	12	0.120	11	2-3/8	25°	.375 x .063	3/8 Sq.	24.81	24.09	23.62	23.15

Hazelthorn

305 - 12 - 21 - 2	12	12	0.083	14	2	25°	.375 x .063	1/4 Rd.	20.91	20.31	19.91	19.50
305 - 12 - 24 - 13	12	12	0.095	13	2	25°	.375 x .063	1/4 Rd.	22.11	21.49	21.07	20.64
305 - 12 - 28 - 4	12	12	0.109	12	2	25°	.375 x .063	1/4 Rd.	23.13	22.46	22.02	21.59
305 - 12 - 30 - 5	12	12	0.120	11	2	25°	.375 x .063	1/4 Rd.	24.81	24.09	23.62	23.15

Brewer, Woodcraft, Quality

305 - 12 - 21 - 3	12	12	0.083	14	2-15/16	25°	.375 x .063	**	20.91	20.31	19.91	19.50
305 - 12 - 24 - 14	12	12	0.095	13	2-15/16	25°	.375 x .063	**	22.11	21.49	21.07	20.64
305 - 12 - 28 - 15	12	12	0.109	12	2-15/16	25°	.375 x .063	**	23.13	22.46	22.02	21.59
305 - 12 - 30 - 6	12	12	0.120	11	2-15/16	25°	.375 x .063	**	24.81	24.09	23.62	23.15
355 - 14 - 30 - 10	14	14	0.120	11	2-1/2	30°	.375 x .063	**	31.60	30.69	30.10	29.50
405 - 16 - 34 - 7	16	16	0.134	10	2-1/2	30°	.375 x .063	**	37.39	36.32	35.60	34.90

*Above Brewer Bodies have one 1/2" KW (Rd.) and two 3/8" KW (Rd.) to fit both old and new machine

Cornell

305 - 12 - 21 - 31	12	12	0.083	14	3 1/2	25°	.375 x .063	PH 3/8 on 4-3/8"	20.91	20.31	19.91	19.50
305 - 12 - 24 - 49	12	12	0.095	13	3 1/2	25°	.375 x .063	PH 3/8 on 4-3/8"	22.11	21.49	21.07	20.64
355 - 16 - 21 - 2	14	16	0.083	14	4	30°	.375 x .063	PH 7/16 on 5"	25.02	24.31	23.83	23.36
355 - 16 - 24 - 5	14	16	0.095	13	4	30°	.375 x .063	PH 7/16 on 5"	26.35	25.59	25.08	24.59
355 - 16 - 30 - 7	14	16	0.120	11	4	30°	.375 x .063	PH 7/16 on 5"	33.33	32.36	31.73	31.10



Stock Price List

\$50 Minimum Order

Saws for Non-Ferrous Metals / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket		Special	Quantities / Price \$US Each			
			.000"	Gauge			(Inches)	(Inches)		1-5	6-49	50-99	100+
102 - 18 - 22 - 1	4	18	0.087	14	3/4	0°	.236 x .063	NO SLOTS		11.89	10.90	10.41	9.91
102 - 30 - 22 - 1	4	30	0.087	14	3/4	0°	.236 x .063	NO SLOTS		12.31	11.28	10.76	10.25
205 - 60 - 22 - 5	8	60	0.087	14	5/8	0°	.236 x .063	3 CU		18.80	17.24	16.45	15.66
255 - 72 - 24 - 2	10	72	0.094	13	5/8	6 Neg.	.236 x .063	4 CU		23.70	21.72	20.73	19.75
255 - 72 - 24 - 3	10	72	0.094	13	5/8	0°	.236 x .063	4 CU		23.70	21.72	20.73	19.75
255 - 80 - 22 - 4	10	80	0.087	14	5/8	6 Neg.	.236 x .063	4 CU		23.13	21.19	20.24	19.27
255 - 80 - 22 - 7	10	80	0.087	14	5/8	2 Neg.	.236 x .063	4 CU		23.13	21.19	20.24	19.27
255 - 100 - 22 - 1	10	100	0.087	14	5/8	2 Neg.	.220 x .051	4 CU		26.69	24.47	23.36	22.24
255 - 100 - 24 - 1	10	100	0.094	13	5/8	0°	.220 x .063	NO SLOTS		26.23	24.04	22.95	21.86
305 - 90 - 30 - 2	12	90	0.118	11	5/8	0°	.236 x .063	6 CU		37.48	34.35	32.80	31.23
305 - 100 - 24 - 3	12	100	0.094	13	1	6 Neg.	.236 x .063	4 CU		30.64	28.07	26.81	25.53
355 - 90 - 30 - 2	14	90	0.118	11	1	2 Neg.	.236 x .063	4 CU		42.76	39.19	37.41	35.64
380 - 100 - 22 - 3	15	100	0.087	14	1	0°	.236 x .063	4 CU		40.50	37.12	35.44	33.75
405 - 100 - 30 - 2	16	100	0.118	11	1	2 Neg.	.236 x .063	4 CU		50.77	46.55	44.42	42.32
505 - 120 - 34 - 1	20	120	0.134	10	1	0°	.252 x .079	4 CU		79.38	72.78	69.46	66.16



Stock Price List

S-08-2008

\$50 Minimum Order

Combination (Planer Style) Saws/ Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Seat Pocket			Quantities / Price \$US Each			
			.000"	Gauge		Hook	(Inches)	Special	1-5	6-20	21-49	50+
185 - 40 - 22 - 1	7-1/4	40	0.087	14	5/8 SKIL	15°	.236 x .063	SKIL	17.92	16.43	15.67	14.93
205 - 40 - 22 - 1	8	40	0.087	14	5/8	15°	.236 x .063		16.22	14.86	14.18	13.50
255 - 50 - 24 - 1	10	50	0.094	13	5/8	15°	.236 x .063		20.18	18.50	17.66	16.82
305 - 60 - 28 - 1	12	60	0.110	12	1	15°	.236 x .063		30.28	27.76	26.50	25.23
355 - 70 - 30 - 1	14	70	0.118	11	1	15°	.236 x .063		38.88	35.65	34.02	32.41
405 - 80 - 30 - 1	16	80	0.118	11	1	15°	.236 x .063		47.15	43.21	41.25	39.28

Thin-Rimmed Saws / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Seat Pocket			Quantities / Price \$US Each			
			.000"	Gauge		Hook	(Inches)	Special	1-5	6-20	21-49	50+
205 - 60 - 22 - 3	8	60	0.087	14	5/8	5°	.236 x .063	RIM .056	40.87	37.46	35.77	34.06
255 - 80 - 22 - 3	10	80	0.087	14	5/8	5°	.236 x .063	RIM .056	43.47	39.85	38.04	36.23

Metric Saws / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Millimeters)	Number of Teeth	Thickness		Bore (Millimeters)	Seat Pocket			Quantities / Price \$US Each			
			.000"	Gauge		Hook	(Inches)	Special	1-5	6-20	21-49	50+
125 - 24 - 28 - 2	125	24	0.110	12	45.0	8°	.327 x .055	NO SLOTS/GIBEN	15.69	14.38	13.73	13.08
220 - 64 - 20 - 1	220	64	0.079		30.0	10°	.236 x .055	2/PH, VAR.MFG.	21.37	19.60	18.70	17.81
300 - 72 - 22 - 36	300	72	0.087	14	30.0	10°	.327 x .055	4/CU, VAR.MFG.	31.57	28.93	27.61	26.30
300 - 96 - 22 - 28	300	96	0.087	14	30.0	10°	.236 x .055	4/CU, VAR.MFG.	32.45	29.74	28.39	27.04
400 - 60 - 28 - 3	400	60	0.110	12	75.0	10°	.323 x .055	6/CU+CS, GIBEN	46.60	42.72	40.77	38.84



Stock Price List

\$50 Minimum Order

Panel Saws / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Millimeters)	Number of Teeth	Thickness		Bore (Millimeters)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	(Millimeters)					1-5	6-20	21-49	50+
125 - 24 - 28 - 2	125	24	0.110	2.8	45.0	8°	.327 x .055	NO SLOTS/GIBEN	15.69	14.38	13.73	13.08
160 - 36 - 32 - 5	160	36	0.126	3.2	55.0	8°	.244 x .063	No Slots, PH3/7/66, Var.Mfg.	28.14	25.79	24.62	23.45
180 - 36 - 35 - 5	180	36	0.138	3.5	45.0	8°	.315 x .063	No Slots, Holzma	26.47	24.25	23.15	22.06
200 - 36 - 32 - 10	200	36	0.126	3.2	20.0	8°	.315 x .063	3/CU, Var.Mfg.	23.94	21.94	20.94	19.95
200 - 36 - 32 - 11	200	36	0.126	3.2	65.0	8°	.315 x .063	3/CU,PH.2/9/100, Var.Mfg.	25.47	23.35	22.30	21.23
200 - 36 - 35 - 17	200	36	0.138	3.5	45.0	8°	.331 x .055	3/CU, Holzma	30.33	27.80	26.54	25.28
200 - 36 - 40 - 5	200	36	0.157	4.0	45.0	8°	.244 x .063	3/CU,PH.2/14/65, Var.Mfg.	54.80	50.23	47.94	45.67
220 - 64 - 20 - 1	220	64	0.079	2.0	30.0	10°	.236 x .055	2/PH, Var.Mfg.	21.37	19.60	18.70	17.81
300 - 72 - 22 - 36	300	72	0.087	2.2	30.0	10°	.327 x .055	4/CU,PH 2/7/42&2/10/60Var.Mfg.	31.57	28.93	27.61	26.30
300 - 96 - 22 - 28	300	96	0.087	2.2	30.0	10°	.236 x .055	4/CU, Var.Mfg.	32.45	29.74	28.39	27.04
350 - 72 - 30 - 19	350	72	0.118	3.0	30.0	10°	.236 x .063	4/CU,PH.2/10/60, Var.Mfg.	43.93	40.27	38.44	36.60
380 - 72 - 35 - 10	380	72	0.138	3.5	60.0	10°	.244 x .063	4/CU,PH.2/10/80, Holzma	60.75	55.68	53.16	50.62
380 - 72 - 35 - 12	380	72	0.138	3.5	60.0	15	.244 x .063	4/CU,PH.2/14/100	60.75	55.68	53.16	50.62
400 - 60 - 28 - 3	400	60	0.110	2.8	75.0	10°	.323 x .055	6/CU+CS, GIBEN	46.60	42.72	40.77	38.84
400 - 72 - 32 - 22	400	72	0.126	3.2	30.0	15°	.244 x .063	4/CU, Var.Mfg.	51.46	47.18	45.03	42.88
400 - 72 - 32 - 23	400	72	0.126	3.2	75.0	15°	.244 x .063	4/CU,PH.4/15/105, Var.Mfg.	52.82	48.42	46.22	44.01
420 - 72 - 35 - 4	420	72	0.138	3.5	60.0	15°	.244 x .063	4/CU, Holzma	72.55	66.49	63.48	60.46
450 - 72 - 35 - 12	450	72	0.138	3.5	60.0	15°	.272 x .063	4/CU,PH.2/14/125, Holzma	75.64	69.33	66.18	63.03
500 - 72 - 35 - 9	500	72	0.138	3.5	60.0	15°	.280 x .063	6/CU,PH.2/11/115, Holzma	83.26	76.33	72.86	69.39
600 - 60 - 40 - 6	600	60	0.157	4.0	60.0	15°	.280 x .055	6/CU,PH.2/11/115 & 2/19/120,Var.Mfg.	119.70	109.73	104.74	99.76



Stock Price List

\$50 Minimum Order

Round Saw Blanks: Ground, Tensioned, Straightened, Not Toothed

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Quantities / Price \$US Each			
			.000"	Gauge		1-5	6-20	21-49	50+
100 - 00 - 16 - 1	4.000	0	0.063	16	5/8	6.74	6.19	5.91	5.62
100 - 00 - 18 - 1	4.000	0	0.071	15	5/8	7.23	6.64	6.33	6.03
100 - 00 - 22 - 1	4.000	0	0.087	14	5/8	7.44	6.82	6.51	6.20
100 - 00 - 24 - 1	4.000	0	0.094	13	5/8	7.89	7.22	6.90	6.57
100 - 00 - 28 - 1	4.000	0	0.110	12	5/8	8.92	8.17	7.80	7.43
100 - 00 - 30 - 1	4.000	0	0.118	11	5/8	9.60	8.80	8.40	8.00
100 - 00 - 34 - 1	4.000	0	0.134	10	5/8	10.29	9.44	9.00	8.58
125 - 00 - 22 - 1	5.000	0	0.087	14	5/8	8.34	7.66	7.30	6.96
125 - 00 - 28 - 1	5.000	0	0.110	12	5/8	10.68	9.79	9.34	8.90
150 - 00 - 16 - 1	6.000	0	0.063	16	5/8	8.61	7.89	7.53	7.18
150 - 00 - 18 - 1	6.000	0	0.071	15	5/8	8.95	8.21	7.83	7.45
150 - 00 - 22 - 1	6.000	0	0.087	14	5/8	9.35	8.57	8.19	7.79
150 - 00 - 24 - 1	6.000	0	0.094	13	5/8	10.34	9.48	9.04	8.61
150 - 00 - 28 - 1	6.000	0	0.110	12	5/8	11.32	10.38	9.90	9.44
150 - 00 - 30 - 1	6.000	0	0.118	11	5/8	11.80	10.82	10.33	9.83
150 - 00 - 34 - 1	6.000	0	0.134	10	5/8	12.33	11.29	10.79	10.27
180 - 00 - 18 - 1	7.000	0	0.071	15	5/8	10.40	9.52	9.10	8.66
180 - 00 - 22 - 1	7.000	0	0.087	14	5/8	11.89	10.90	10.40	9.90
180 - 00 - 24 - 1	7.000	0	0.094	13	5/8	12.86	11.79	11.26	10.72
180 - 00 - 28 - 1	7.000	0	0.110	12	5/8	13.86	12.70	12.12	11.55
180 - 00 - 30 - 1	7.000	0	0.118	11	5/8	15.82	14.51	13.86	13.19
205 - 00 - 14 - 1	8.000	0	0.055	17	5/8	12.35	11.33	10.82	10.30
205 - 00 - 16 - 1	8.000	0	0.063	16	5/8	12.13	11.12	10.61	10.12
205 - 00 - 18 - 1	8.000	0	0.071	15	5/8	11.50	10.55	10.06	9.59
205 - 00 - 22 - 1	8.000	0	0.087	14	5/8	10.51	9.64	9.20	8.76
205 - 00 - 24 - 1	8.000	0	0.094	13	5/8	12.03	11.03	10.53	10.03
205 - 00 - 28 - 1	8.000	0	0.110	12	5/8	13.02	11.94	11.40	10.86
205 - 00 - 30 - 1	8.000	0	0.118	11	5/8	13.72	12.58	11.99	11.43
205 - 00 - 34 - 1	8.000	0	0.134	10	5/8	14.63	13.41	12.81	12.19
230 - 00 - 22 - 1	9.000	0	0.087	14	5/8	13.42	12.31	11.75	11.19
230 - 00 - 24 - 1	9.000	0	0.094	13	5/8	15.20	13.94	13.31	12.67
255 - 00 - 14 - 1	10.000	0	0.055	17	5/8	14.28	13.09	12.49	11.90



Stock Price List

\$50 Minimum Order

Round Saw Blanks: Ground, Tensioned, Straightened, Not Toothed

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Quantities / Price \$US Each			
			.000"	Gauge		1-5	6-20	21-49	50+
255 - 00 - 16 - 1	10.000	0	0.063	16	5/8	14.35	13.16	12.56	11.96
255 - 00 - 18 - 1	10.000	0	0.071	15	5/8	13.33	12.21	11.66	11.11
255 - 00 - 22 - 1	10.000	0	0.087	14	5/8	14.08	12.89	12.31	11.73
255 - 00 - 24 - 1	10.000	0	0.094	13	5/8	14.92	13.67	13.05	12.43
255 - 00 - 28 - 1	10.000	0	0.110	12	5/8	18.77	17.20	16.41	15.64
255 - 00 - 30 - 1	10.000	0	0.118	11	5/8	19.78	18.14	17.32	16.49
255 - 00 - 34 - 1	10.000	0	0.134	10	5/8	21.15	19.39	18.52	17.63
305 - 00 - 22 - 1	12.000	0	0.087	14	1	18.77	17.20	16.42	15.64
305 - 00 - 24 - 1	12.000	0	0.094	13	1	19.25	17.65	16.86	16.04
305 - 00 - 24 - 2	12.000	0	0.094	13	5/8	19.25	17.65	16.86	16.04
305 - 00 - 28 - 1	12.000	0	0.110	12	1	22.29	20.42	19.50	18.57
305 - 00 - 30 - 1	12.000	0	0.118	11	1	23.58	21.61	20.63	19.64
305 - 00 - 34 - 1	12.000	0	0.134	10	1	25.60	23.46	22.40	21.33
355 - 00 - 22 - 1	14.000	0	0.087	14	1	23.15	21.22	20.25	19.29
355 - 00 - 24 - 1	14.000	0	0.094	13	1	25.65	23.51	22.45	21.38
355 - 00 - 28 - 1	14.000	0	0.110	12	1	28.92	26.51	25.30	24.10
355 - 00 - 30 - 1	14.000	0	0.118	11	1	30.13	27.62	26.36	25.10
355 - 00 - 34 - 1	14.000	0	0.134	10	1	33.10	30.34	28.97	27.59
405 - 00 - 28 - 1	16.000	0	0.110	12	1	33.99	31.17	29.74	28.32
405 - 00 - 30 - 1	16.000	0	0.118	11	1	35.77	32.78	31.30	29.81
405 - 00 - 34 - 1	16.000	0	0.134	10	1	37.92	34.74	33.18	31.59
455 - 00 - 30 - 1	18.000	0	0.118	11	1	47.43	43.48	41.50	39.53
455 - 00 - 34 - 1	18.000	0	0.134	10	1	50.92	46.67	44.55	42.44
510 - 00 - 30 - 1	20.000	0	0.118	11	1	57.03	52.27	49.90	47.53
510 - 00 - 34 - 1	20.000	0	0.134	10	1	58.54	53.66	51.22	48.78
560 - 00 - 34 - 1	22.000	0	0.134	10	1	78.20	71.69	68.43	65.17
610 - 00 - 34 - 1	24.000	0	0.134	10	1	103.27	94.67	90.37	86.07
610 - 00 - 38 - 1	24.000	0	0.150	9	1	109.92	100.76	96.19	91.60
610 - 00 - 45 - 1	24.000	0	0.177	7	1	138.05	126.53	120.80	115.03
660 - 00 - 38 - 1	26.000	0	0.150	9	1	149.03	136.61	130.40	124.19



Stock Price List

\$50 Minimum Order

Groover Bodies: Toothed & Round Blanks - for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness (Inches)	Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
								1-5	6-20	21-49	50+
100 - 00 - 32 - 1	4.000	0	1/8	5/8				12.85	11.78	11.25	10.71
100 - 00 - 48 - 1	4.000	0	3/16	5/8				21.09	19.33	18.45	17.57
100 - 00 - 64 - 1	4.000	0	1/4	5/8				22.31	20.45	19.53	18.60
125 - 00 - 32 - 1	5.000	0	1/8	5/8				15.33	14.05	13.41	12.78
125 - 00 - 48 - 1	5.000	0	3/16	5/8				24.16	22.16	21.15	20.15
125 - 00 - 64 - 1	5.000	0	1/4	5/8				25.53	23.40	22.33	21.28
125 - 00 - 79 - 1	5.000	0	5/16	5/8			20 HRC	27.97	25.63	24.47	23.31
125 - 06 - 32 - 1	5.000	6	1/8	5/8	15°	.331 x .063		18.69	17.15	16.35	15.58
150 - 00 - 32 - 1	6.000	0	1/8	5/8				17.96	16.48	15.72	14.97
150 - 00 - 48 - 1	6.000	0	3/16	5/8				28.42	26.04	24.85	23.68
150 - 00 - 64 - 1	6.000	0	1/4	5/8				29.49	27.04	25.81	24.58
150 - 00 - 79 - 1	6.000	0	5/16	5/8			20 HRC	32.18	29.50	28.15	26.82
150 - 00 - 95 - 1	6.000	0	3/8	5/8			20 HRC	33.95	31.12	29.70	28.29
150 - 00 - 111 - 1	6.000	0	7/16	5/8			20 HRC	35.96	32.95	31.46	29.96
150 - 00 - 127 - 1	6.000	0	1/2	5/8			20 HRC	37.39	34.27	32.72	31.15
150 - 04 - 32 - 1	6.000	4	1/8	5/8	15°	.331 x .063		20.70	18.98	18.11	17.25
150 - 04 - 48 - 1	6.000	4	3/16	5/8	15°	.331 x .063		34.67	31.79	30.34	28.89
150 - 06 - 32 - 1	6.000	6	1/8	5/8	15°	.331 x .063		21.42	19.64	18.76	17.86
150 - 06 - 48 - 1	6.000	6	3/16	5/8	15°	.331 x .063		34.67	31.79	30.34	28.89
150 - 08 - 48 - 2	6.000	8	3/16	5/8	15°	.331 x .063		34.67	31.79	30.34	28.89
150 - 08 - 79 - 1	6.000	8	5/16	5/8	15°	.331 x .063	20 HRC	41.81	38.33	36.59	34.85
150 - 08 - 111 - 1	6.000	8	7/16	5/8	15°	.331 x .063	20 HRC	53.16	48.74	46.53	44.31
201 - 00 - 32 - 1	8.000	0	1/8	5/8				18.84	17.27	16.49	15.70
201 - 00 - 48 - 1	8.000	0	3/16	5/8				33.42	30.62	29.23	27.84
201 - 00 - 64 - 1	8.000	0	1/4	5/8				35.83	32.86	31.35	29.87
201 - 00 - 79 - 1	8.000	0	5/16	5/8			20 HRC	38.27	35.09	33.50	31.89
201 - 00 - 95 - 1	8.000	0	3/8	5/8			20 HRC	42.47	38.93	37.16	35.39
201 - 00 - 111 - 1	8.000	0	7/16	5/8			20 HRC	46.16	42.32	40.39	38.47
201 - 00 - 127 - 1	8.000	0	1/2	5/8			20 HRC	49.01	44.93	42.88	40.84
201 - 08 - 64 - 1	8.000	8	1/4	5/8	15°	.331 x .063		42.85	39.27	37.49	35.71
201 - 08 - 95 - 1	8.000	8	3/8	5/8	15°	.331 x .063	20 HRC	52.70	48.31	46.10	43.92
201 - 08 - 111 - 1	8.000	8	7/16	5/8	15°	.331 x .063	20 HRC	66.34	60.81	58.05	55.29
201 - 08 - 127 - 1	8.000	8	1/2	5/8	15°	.331 x .063	20 HRC	70.31	64.46	61.53	58.59



Stock Price List

\$50 Minimum Order

Groover Bodies: Toothed & Round Blanks - for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness (Inches)	Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
								1-5	6-20	21-49	50+
201 - 12 - 32 - 1	8.000	12	1/8	5/8	15°	.331 x .063		23.49	21.53	20.56	19.57
201 - 12 - 48 - 1	8.000	12	3/16	5/8	15°	.331 x .063		40.31	36.95	35.27	33.59
201 - 12 - 64 - 1	8.000	12	1/4	5/8	15°	.331 x .063		43.80	40.16	38.33	36.51
201 - 24 - 48 - 1	8.000	24	3/16	5/8	15°	.331 x .063		42.61	39.07	37.28	35.51
201 - 24 - 64 - 1	8.000	24	1/4	5/8	15°	.331 x .063		46.90	43.00	41.03	39.08
251 - 00 - 32 - 1	10.000	0	1/8	1				23.83	21.83	20.85	19.85
251 - 00 - 48 - 1	10.000	0	3/16	1				47.94	43.95	41.95	39.95
251 - 00 - 64 - 1	10.000	0	1/4	1				50.45	46.25	44.15	42.04
251 - 00 - 79 - 1	10.000	0	5/16	1			20 HRC	54.34	49.81	47.54	45.29
251 - 00 - 95 - 1	10.000	0	3/8	1			20 HRC	57.01	52.26	49.89	47.51
251 - 00 - 111 - 1	10.000	0	7/16	1			20 HRC	63.48	58.19	55.55	52.90
251 - 00 - 127 - 1	10.000	0	1/2	1			20 HRC	68.29	62.61	59.75	56.91
252 - 12 - 32 - 1	10.000	12	1/8	1	15°	.331 x .063		28.47	26.09	24.91	23.72
252 - 12 - 48 - 1	10.000	12	3/16	1	15°	.331 x .063		51.58	47.28	45.14	42.99
252 - 12 - 64 - 1	10.000	12	1/4	1	15°	.331 x .063		56.90	52.15	49.78	47.41
252 - 12 - 79 - 1	10.000	12	5/16	1	15°	.331 x .063	20 HRC	61.03	55.94	53.41	50.85
252 - 12 - 95 - 1	10.000	12	3/8	1	15°	.331 x .063	20 HRC	66.59	61.03	58.25	55.49
252 - 12 - 111 - 1	10.000	12	7/16	1	15°	.331 x .063	20 HRC	76.27	69.92	66.73	63.56
252 - 24 - 32 - 1	10.000	24	1/8	1	15°	.331 x .063		30.07	27.58	26.32	25.07
252 - 24 - 48 - 1	10.000	24	3/16	1	15°	.331 x .063		51.58	47.28	45.14	42.99
252 - 24 - 64 - 1	10.000	24	1/4	1	15°	.331 x .063		56.90	52.15	49.78	47.41
252 - 24 - 79 - 1	10.000	24	5/16	1	15°	.331 x .063	20 HRC	65.00	59.58	56.88	54.17
252 - 24 - 95 - 1	10.000	24	3/8	1	15°	.331 x .063	20 HRC	71.09	65.17	62.22	59.25
252 - 24 - 111 - 1	10.000	24	7/16	1	15°	.331 x .063	20 HRC	76.27	69.92	66.73	63.56
252 - 24 - 127 - 1	10.000	24	1/2	1	15°	.331 x .063	20 HRC	82.62	75.73	72.29	68.85
302 - 00 - 32 - 1	12.000	0	1/8	1				31.23	28.62	27.32	26.02
302 - 00 - 48 - 1	12.000	0	3/16	1				64.16	58.82	56.13	53.46
302 - 00 - 64 - 1	12.000	0	1/4	1				68.57	62.86	60.00	57.14
302 - 00 - 79 - 1	12.000	0	5/16	1			20 HRC	73.27	67.16	64.11	61.05
302 - 00 - 95 - 1	12.000	0	3/8	1			20 HRC	81.22	74.46	71.07	67.69
302 - 00 - 111 - 1	12.000	0	7/16	1			20 HRC	87.76	80.44	76.79	73.13
302 - 00 - 127 - 1	12.000	0	1/2	1			20 HRC	97.46	89.34	85.28	81.22



Stock Price List

\$50 Minimum Order

Groover Bodies: Toothed & Round Blanks - for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness (Inches)	Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
								1-5	6-20	21-49	50+
303 - 24 - 48 - 1	12.000	24	3/16	1	15°	.331 x .063		67.85	62.19	59.37	56.55
303 - 24 - 64 - 1	12.000	24	1/4	1	15°	.331 x .063		73.49	67.37	64.31	61.24
303 - 24 - 79 - 1	12.000	24	5/16	1	15°	.331 x .063	20 HRC	83.09	76.16	72.70	69.24
303 - 24 - 95 - 1	12.000	24	3/8	1	15°	.331 x .063	20 HRC	92.06	84.38	80.55	76.71
303 - 24 - 111 - 1	12.000	24	7/16	1	15°	.331 x .063	20 HRC	108.32	99.30	94.78	90.28
353 - 00 - 48 - 1	14.000	0	3/16	1				84.01	77.00	73.50	70.00
353 - 00 - 64 - 1	14.000	0	1/4	1				92.52	84.82	80.96	77.11
353 - 00 - 79 - 1	14.000	0	5/16	1			20 HRC	100.75	92.35	88.15	83.96
353 - 00 - 95 - 1	14.000	0	3/8	1			20 HRC	110.35	101.14	96.55	91.95



Stock Price List

\$50 Minimum Order

Split-Scoring Saw Sets: Ready for Carbide Tipping

Catalog Number	Diameter (Millimeters)	Number of Teeth	Thickness		Bore (Millimeters)	Hook	Special	Quantities / Price \$US Each			
			.000"	(mm)				25-49	50-99	100-249	250+
80 - 10 - 20 - S20	80	10	0.079	2.0	20.0	12°	RIM .040/2PH	33.88	31.36	29.81	28.23
100 - 12 - 20 - S20	100	12	0.079	2.0	20.0	12°	RIM .040/2PH	33.88	31.36	29.81	28.23
100 - 12 - 20 - S22	100	12	0.079	2.0	22.0	12°	RIM .040/2PH	33.88	31.36	29.81	28.23
105 - 12 - 20 - S20	105	12	0.079	2.0	20.0	12°	RIM .040/2PH	34.34	31.80	30.21	28.62
120 - 12 - 20 - S20	120	12	0.079	2.0	20.0	12°	RIM .040/2PH	34.99	32.40	30.77	29.16
120 - 12 - 20 - S22	120	12	0.079	2.0	22.0	12°	RIM .040/2PH	34.99	32.40	30.77	29.16
125 - 12 - 20 - S20	125	12	0.079	2.0	20.0	12°	RIM .040/2PH	35.65	33.01	31.35	29.70
125 - 12 - 20 - S22	125	12	0.079	2.0	22.0	12°	RIM .040/2PH	35.65	33.01	31.35	29.70
160 - 16 - 20 - S20	160	16	0.079	2.0	20.0	12°	RIM .040/2PH	45.08	41.76	39.66	37.58
160 - 16 - 20 - S30	160	16	0.079	2.0	30.0	12°	RIM .040/2PH	45.08	41.76	39.66	37.58
180 - 18 - 20 - S30	180	18	0.079	2.0	30.0	12°	RIM .040/2PH	52.64	48.74	46.30	43.87



Stock Price List

\$50 Minimum Order

Parquet Saws: Hard Chromium Plated, Ready to Use

Catalog Number	Diameter (Millimeters)	Number of teeth	Thickness		Bore (Millimeters)	Hook	Special	Quantities / Price \$US Each			
			.000"	(Millimeters)				1-5	6-20	21-49	50+
250 - 52 - 16 - 2	250	52	0.063	1.6	75	10°	PARQUET SAW	39.82	36.51	34.85	33.19
250 - 52 - 25 - 5	250	52	0.098	2.5	75	10°	PARQUET SAW	48.98	44.90	42.86	40.81

Saw Bushings: OD Knurled for Perfect Press Fit

Catalog Number	Outside Diameter	Inside Diameter	Thickness		Special	Quantities / Price \$US Each			
			Gage	Millimeters		25-49	50-99	100-249	250+
16 - 10 - 16 - 1	5/8	3/8	16	1.6	BUSHING	2.77	2.46	2.08	1.98
16 - 10 - 22 - 1	5/8	3/8	14	2.2	BUSHING	2.77	2.46	2.08	1.98
16 - 10 - 28 - 1	5/8	3/8	12	2.8	BUSHING	2.77	2.46	2.08	1.98
16 - 13 - 16 - 1	5/8	1/2	6	1.6	BUSHING	2.77	2.46	2.08	1.98
16 - 13 - 22 - 1	5/8	1/2	14	2.2	BUSHING	2.77	2.46	2.08	1.98
16 - 13 - 28 - 1	5/8	1/2	12	2.8	BUSHING	2.77	2.46	2.08	1.98
25 - 16 - 16 - 1	1	5/8	16	1.6	BUSHING	2.97	2.62	2.23	2.12
25 - 16 - 22 - 1	1	5/8	14	2.2	BUSHING	2.97	2.62	2.23	2.12
25 - 16 - 28 - 1	1	5/8	12	2.8	BUSHING	2.97	2.62	2.23	2.12
25 - 16 - 34 - 1	1	5/8	10	3.4	BUSHING	2.97	2.62	2.23	2.12
25 - 19 - 16 - 1	1	3/4	16	1.6	BUSHING	2.97	2.62	2.23	2.12
25 - 19 - 22 - 1	1	3/4	14	2.2	BUSHING	2.97	2.62	2.23	2.12
25 - 19 - 28 - 1	1	3/4	12	2.8	BUSHING	2.97	2.62	2.23	2.12
25 - 19 - 34 - 1	1	3/4	10	3.4	BUSHING	2.97	2.62	2.23	2.12



Stock Price List

\$50 Minimum Order

Dado Sets: Ready for Carbide Tipping, Pocket Size .065 X .235"

- Each Set Consists of
 - One Outer Saw - Thin Rimmed, Right Hand
 - One Outer Saw - Thin Rimmed, Left Hand
 - One Dado Filler - 1/16" Thick with 2 Teeth
 - Two Dado Fillers - 1/8" Thick with 2 Teeth Each
 - One Dado Filler - 1/4" Thick with 2 Teeth
 - One sturdy wooden box for set

Catalog Number	Diameter (Inches)	Thickness		Bore		Seat Pocket		Special	Quantities / Price \$US Each			
		.000"	Gauge	(Inches)	Hook	(Inches)			1-5	6-20	21-49	50+
152 - 18 - 27 - DD1	6	S=.106	12	5/8	15°	.236 x .063		SAW RIM = .087	104.02	99.39	94.76	92.46
203 - 24 - 27 - DD1	8	S=.106	12	5/8	15°	.236 x .055		SAW RIM = .087	124.55	119.01	113.47	110.70
203 - 24 - 27 - DD2	8	S=.106	12	1	15°	.236 x .063		SAW RIM = .087	130.46	124.66	118.86	115.97
203 - 40 - 27 - DD1	8	S=.106	12	5/8	15°	.236 x .063		SAW RIM = .087	128.93	123.20	117.46	114.61
250 - 24 - 27 - DD1	10	S=.106	12	5/8	15°	.236 x .055		SAW RIM = .087	145.45	139.00	132.54	129.29
250 - 24 - 27 - DD2	10	S=.106	12	1	15°	.236 x .055		SAW RIM = .087	153.35	146.54	139.73	136.31
250 - 60 - 27 - DD1	10	S=.106	12	5/8	15°	.236 x .063		SAW RIM = .087	154.86	147.98	141.09	137.66
305 - 24 - 27 - DD1	12	S=.106	12	1	15°	.236 x .063		SAW RIM = .087	190.00	181.56	173.12	168.89
355 - 40 - 28 - DD1	14	S=.110	12	1	15°	.236 x .063		SAW RIM = .087	221.79	211.95	202.08	197.14

"S=" Indicates teeth and thickness of outer saws.
Single dado fillers: See next page

Stock Price List

\$50 Minimum Order

Dado Fillers, Ready for Carbide Tipping

Catalog Number	Diameter (Inches)	Number Of Teeth	Thickness (Inches)	Bore (Inches)	Hook	Seat Pocket (Inches)	Quantities / Price \$US Each			
							1-5	6-20	21-49	50+
152 - 02 - 16 - 1	6	2	1/16	5/8	15°	.236 x .059	7.14	6.53	6.23	5.95
152 - 02 - 32 - 1	6	2	1/8	5/8	15°	.236 x .059	9.11	8.36	7.97	7.59
152 - 02 - 64 - 1	6	2	1/4	5/8	15°	.236 x .059	16.46	15.08	14.40	13.71
203 - 02 - 16 - 1	8	2	1/16	5/8	15°	.236 x .059	8.73	8.00	7.64	7.27
203 - 02 - 32 - 1	8	2	1/8	5/8	15°	.236 x .059	10.86	9.96	9.50	9.04
203 - 02 - 64 - 1	8	2	1/4	5/8	15°	.236 x .059	19.10	17.50	16.71	15.92
203 - 02 - 16 - 2	8	2	1/16	1	15°	.236 x .059	9.15	8.40	8.02	7.62
203 - 02 - 32 - 2	8	2	1/8	1	15°	.236 x .059	11.24	10.30	9.83	9.36
203 - 02 - 64 - 2	8	2	1/4	1	15°	.236 x .059	19.56	17.94	17.11	16.31
250 - 02 - 16 - 1	10	2	1/16	5/8	15°	.236 x .059	10.58	9.71	9.27	8.82
250 - 02 - 32 - 1	10	2	1/8	5/8	15°	.236 x .059	12.85	11.78	11.25	10.71
250 - 02 - 64 - 1	10	2	1/4	5/8	15°	.236 x .059	22.23	20.39	19.46	18.53
250 - 02 - 16 - 2	10	2	1/16	1	15°	.236 x .059	11.03	10.12	9.65	9.19
250 - 02 - 32 - 2	10	2	1/8	1	15°	.236 x .063	13.26	12.16	11.60	11.05
250 - 02 - 64 - 2	10	2	1/4	1	15°	.236 x .059	22.71	20.82	19.87	18.93
305 - 02 - 16 - 1	12	2	1/16	1	15°	.236 x .059	15.19	13.93	13.29	12.66
305 - 02 - 32 - 1	12	2	1/8	1	15°	.236 x .059	19.02	17.43	16.64	15.85
305 - 02 - 64 - 1	12	2	1/4	1	15°	.236 x .059	29.70	27.23	26.00	24.76
355 - 02 - 16 - 1	14	2	1/16	1	15°	.236 x .059	16.51	15.13	14.44	13.75
355 - 02 - 32 - 1	14	2	1/8	1	15°	.236 x .059	20.60	18.87	18.03	17.17
355 - 02 - 64 - 1	14	2	1/4	1	15°	.236 x .059	32.02	29.35	28.00	26.68

Use these fillers ONLY with ORIGINAL Grasche DADO Sets
Do NOT use OTHER fillers with ORIGINAL Grasche DADO Sets

Stock Price List

\$50 Minimum Order

Anvils for Saw Straightening with Crowned Precision Surface

Catalog Number	Diameter (Inches)	Height (Inches)	Weight (Pounds)	Price Each
ANVIL - 04 - 05 - 1	4	5	15	378.35
ANVIL - 06 - 06 - 1	6	6	48	679.65
ANVIL - 08 - 06 - 1	8	6	88	1001.65
ANVIL - 10 - 06 - 1	10	6	132	1403.00

Hammers for Saw Straightening with Crowned Precision Surface

Catalog Number	Head Type	Weight (Pounds)	Price Each
HCRPE - 275 - 1	CROSS PEEN	2.75	110.40
HDOHE - 325 - 1	DOGHEAD	3.25	123.05
HCOMB - 225 - 1	COMBINATION	2.25	104.65
HTWFA - 225 - 1	TWIST FACE	2.25	141.45
HTWFA - 325 - 1	TWIST FACE	3.25	196.65

Precision Straight Edges for Flatness Testing

Catalog Number	Item	Length (Inches)	Price Each
STR - EDGE - SET - 1	SET OF FOUR LENGTHS:	7, 9, 11, 13	84.53
STR - EDGE - 16 - 1	INDIVIDUAL:	16	53.48
STR - EDGE - 18 - 1	INDIVIDUAL:	18	53.48
STR - EDGE - 20 - 1	INDIVIDUAL:	20	67.28
STR - EDGE - 22 - 1	INDIVIDUAL:	22	67.28
STR - EDGE - 24 - 1	INDIVIDUAL:	24	72.45

Saw Dial Indicators - Graduation .001"

Catalog Number	Model / Description	Price Each
DIAL - MODEL - A	MODEL A. - LARGE ROUND ANVIL	87.69
DIAL - MODEL - B	MODEL B. - POINTED ANVIL	110.40
DIAL - MODEL - C	MODEL C. - CYLINDRICAL ANVIL	110.40

