



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
102 - 12 - 22 - 1	4	12	0.087	14	3/4	15°	.236 x .063	NO SLOTS	11.53	10.58	10.10	9.61
102 - 12 - 24 - 2	4	12	0.094	13	5/8	15°	.236 x .063	NO SLOTS	11.71	10.73	10.24	9.75
102 - 18 - 22 - 1	4	18	0.087	14	3/4	0°	.236 x .063	NO SLOTS	11.89	10.90	10.41	9.91
102 - 30 - 22 - 1	4	30	0.087	14	3/4	0°	.236 x .063	NO SLOTS	12.31	11.28	10.76	10.25
115 - 24 - 22 - 2	4-1/2	24	0.087	14	3/8	10°	.236 x .055	NO SLOTS	12.77	11.70	11.17	10.64
115 - 40 - 18 - 1	4-1/2	40	0.071	15	3/8	5°	.189 x .051	NO SLOTS	12.40	11.37	10.86	10.34
150 - 16 - 22 - 1	6	16	0.087	14	5/8	15°	.236 x .063		10.96	10.06	9.60	9.14
150 - 30 - 22 - 1	6	30	0.087	14	5/8	10°	.236 x .063		11.75	10.78	10.29	9.80
150 - 40 - 22 - 1	6	40	0.087	14	5/8	5°	.236 x .063		12.44	11.40	10.88	10.36
165 - 24 - 18 - 1	6-1/2	24	0.071	15	5/8 SKIL	15°	.252 x .063	SKIL	13.97	12.80	12.22	11.64
165 - 40 - 18 - 1	6-1/2	40	0.071	15	5/8 SKIL	10°	.236 x .063	SKIL	14.90	13.66	13.03	12.41
180 - 40 - 22 - 1	7	40	0.087	14	5/8	10°	.236 x .063		14.08	12.90	12.33	11.74
185 - 24 - 18 - 1	7-1/4	24	0.071	15	5/8 SKIL	15°	.252 x .063	SKIL	13.03	11.94	11.40	10.86
185 - 40 - 18 - 1	7-1/4	40	0.071	15	5/8 SKIL	10°	.236 x .063	SKIL	13.82	12.66	12.10	11.52
185 - 60 - 18 - 1	7-1/4	60	0.071	15	5/8 SKIL	5°	.236 x .063	SKIL	15.02	13.78	13.14	12.52
205 - 24 - 22 - 1	8	24	0.087	14	5/8	15°	.236 x .063		12.74	11.67	11.14	10.61
205 - 24 - 24 - 1	8	24	0.094	13	5/8	15°	.236 x .063		14.48	13.27	12.66	12.06
205 - 40 - 22 - 2	8	40	0.087	14	5/8	10°	.236 x .063		13.59	12.47	11.89	11.33
205 - 40 - 24 - 5	8	40	0.094	13	5/8	10°	.236 x .063		15.27	14.00	13.36	12.73
205 - 40 - 34 - 2	8	40	0.134	10	5/8	10°	.236 x .063		20.01	18.34	17.50	16.68
205 - 48 - 22 - 1	8	48	0.087	14	5/8	10°	.236 x .063		15.15	13.89	13.25	12.62
205 - 60 - 22 - 1	8	60	0.087	14	5/8	5°	.236 x .063		14.61	13.39	12.78	12.17
205 - 60 - 24 - 1	8	60	0.094	13	5/8	5°	.236 x .063		17.05	15.64	14.93	14.21
205 - 60 - 28 - 1	8	60	0.110	12	5/8	5°	.236 x .063		20.02	18.35	17.53	16.69
205 - 60 - 34 - 1	8	60	0.134	10	5/8	5°	.236 x .063		24.27	22.24	21.24	20.23
230 - 24 - 22 - 1	9	24	0.087	14	5/8	15°	.236 x .063		15.77	14.46	13.79	13.13
230 - 40 - 22 - 2	9	40	0.087	14	5/8	15°	.236 x .063		17.00	15.57	14.88	14.17
230 - 60 - 22 - 2	9	60	0.087	14	5/8	5°	.236 x .063		18.42	16.89	16.13	15.36
230 - 72 - 22 - 1	9	72	0.087	14	5/8	5°	.236 x .063	4 CU	22.24	20.39	19.46	18.54
255 - 24 - 22 - 1	10	24	0.087	14	5/8	20°	.252 x .079		16.18	14.84	14.17	13.49
255 - 24 - 24 - 1	10	24	0.094	13	5/8	20°	.252 x .079		17.00	15.58	14.88	14.17
255 - 24 - 28 - 1	10	24	0.110	12	5/8	20°	.236 x .079		22.07	20.22	19.31	18.39
255 - 30 - 22 - 1	10	30	0.087	14	5/8	20°	.252 x .079		19.40	17.78	16.99	16.17
255 - 30 - 24 - 1	10	30	0.094	13	5/8	20°	.252 x .079		20.23	18.54	17.70	16.86
255 - 40 - 22 - 2	10	40	0.087	14	5/8	15°	.236 x .063	4 CU	20.06	18.38	17.55	16.71



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
255 - 40 - 22 - 3	10	40	0.087	14	5/8	15°	.236 x .063		18.68	17.12	16.34	15.57
255 - 40 - 24 - 2	10	40	0.094	13	5/8	15°	.236 x .063		19.65	18.01	17.20	16.38
255 - 40 - 28 - 1	10	40	0.110	12	5/8	15°	.236 x .063		24.85	22.78	21.75	20.71
255 - 40 - 34 - 1	10	40	0.134	10	5/8	15°	.236 x .063		27.05	24.79	23.68	22.54
255 - 48 - 22 - 1	10	48	0.087	14	5/8	10°	.236 x .063		20.36	18.65	17.80	16.95
255 - 48 - 24 - 1	10	48	0.094	13	5/8	10°	.236 x .063	3 CU	22.46	20.59	19.64	18.72
255 - 60 - 22 - 1	10	60	0.087	14	5/8	10°	.236 x .063		18.11	16.61	15.85	15.10
255 - 60 - 22 - 2	10	60	0.087	14	5/8	10°	.236 x .063	3 CU	20.44	18.73	17.87	17.02
255 - 60 - 24 - 1	10	60	0.094	13	5/8	10°	.236 x .063		20.54	18.83	17.97	17.11
255 - 60 - 24 - 2	10	60	0.094	13	5/8	5°	.236 x .063	4 CU	21.10	19.35	18.47	17.60
255 - 60 - 28 - 2	10	60	0.110	12	5/8	5°	.236 x .063	4 CU	23.99	22.00	21.00	20.00
255 - 60 - 30 - 1	10	60	0.118	11	5/8	10°	.236 x .063		25.08	22.99	21.94	20.90
255 - 60 - 34 - 1	10	60	0.134	10	5/8	10°	.236 x .063		27.75	25.44	24.28	23.13
255 - 80 - 22 - 2	10	80	0.087	14	5/8	5°	.236 x .063	4 CU	20.42	18.72	17.86	17.01
255 - 80 - 24 - 1	10	80	0.094	13	5/8	5°	.236 x .063	4 CU	23.99	22.00	20.99	20.00
255 - 80 - 28 - 2	10	80	0.110	12	5/8	10°	.236 x .063	4 CU	26.94	24.71	23.58	22.46
255 - 80 - 30 - 1	10	80	0.118	11	5/8	5°	.236 x .063		26.58	24.37	23.25	22.15
305 - 12 - 28 - 1	12	12	0.110	12	1	25°	.252 x .087	NO SLOTS	25.52	23.39	22.32	21.26
305 - 24 - 22 - 1	12	24	0.087	14	1	20°	.252 x .063	3 CU	23.83	21.83	20.84	19.85
305 - 24 - 24 - 1	12	24	0.094	13	1	20°	.252 x .079	3 CU	25.23	23.14	22.08	21.03
305 - 24 - 28 - 1	12	24	0.110	12	1	20°	.252 x .079	3 CU	26.39	24.20	23.10	22.00
305 - 24 - 28 - 135	12	24	0.110	12	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	27.26	25.01	23.86	22.71
305 - 24 - 30 - 1	12	24	0.118	11	1	20°	.252 x .079	3 CU	28.26	25.90	24.73	23.55
305 - 24 - 34 - 1	12	24	0.134	10	1	20°	.252 x .079	3 CU	30.45	27.92	26.65	25.38
305 - 30 - 22 - 1	12	30	0.087	14	1	20°	.252 x .079	3 CU	23.93	21.94	20.94	19.94
305 - 30 - 24 - 1	12	30	0.094	13	1	20°	.252 x .079	3 CU	25.19	23.09	22.03	20.99
305 - 30 - 28 - 1	12	30	0.110	12	1	20°	.252 x .079	3 CU	26.92	24.67	23.55	22.44
305 - 30 - 30 - 1	12	30	0.118	11	1	20°	.252 x .079	3 CU	28.51	26.14	24.96	23.76
305 - 30 - 34 - 1	12	30	0.134	10	1	20°	.252 x .079	3 CU	31.33	28.72	27.42	26.12
305 - 36 - 24 - 1	12	36	0.094	13	1	20°	.252 x .079	3 CU	26.53	24.32	23.22	22.11
305 - 36 - 24 - 107	12	36	0.094	13	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	26.39	24.27	23.17	22.08
305 - 36 - 28 - 1	12	36	0.110	12	1	20°	.252 x .079	3 CU	27.29	25.01	23.87	22.74
305 - 36 - 28 - 172	12	36	0.110	12	3 1/8	20°	.252 x .079	Mereen-Johnson Rip	27.26	25.01	23.86	22.71
305 - 36 - 30 - 1	12	36	0.118	11	1	20°	.252 x .079	3 CU	28.96	26.54	25.33	24.13
305 - 36 - 34 - 1	12	36	0.134	10	1	20°	.252 x .079	3 CU	32.18	29.50	28.15	26.82
305 - 40 - 24 - 2	12	40	0.094	13	1	15°	.236 x .063	4 CU	25.47	23.36	22.29	21.23



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
305 - 40 - 28 - 1	12	40	0.110	12	1	15°	.236 x .063	4 CU	28.00	25.68	24.51	23.35
305 - 40 - 30 - 1	12	40	0.118	11	1	15°	.236 x .063	4 CU	28.27	25.90	24.74	23.55
305 - 40 - 34 - 1	12	40	0.134	10	1	15°	.236 x .063	4 CU	33.30	30.54	29.15	27.76
305 - 48 - 24 - 1	12	48	0.094	13	1	15°	.236 x .063	4 CU	26.35	24.14	23.05	21.95
305 - 60 - 24 - 1	12	60	0.094	13	1	10°	.236 x .063	4 CU	26.43	24.23	23.14	22.02
305 - 60 - 24 - 2	12	60	0.094	13	5/8	10°	.236 x .063	4 CU	28.34	25.98	24.79	23.61
305 - 60 - 28 - 2	12	60	0.110	12	1	10°	.236 x .063	4 CU	29.82	27.32	26.08	24.84
305 - 60 - 30 - 1	12	60	0.118	11	1	10°	.236 x .063	4 CU	32.50	29.79	28.44	27.08
305 - 60 - 34 - 1	12	60	0.134	10	1	10°	.236 x .063	4 CU	35.09	32.17	30.71	29.23
305 - 72 - 24 - 1	12	72	0.094	13	1	10°	.236 x .063	4 CU	27.39	25.10	23.97	22.83
305 - 72 - 30 - 1	12	72	0.118	11	1	10°	.236 x .063	4 CU	33.50	30.71	29.30	27.91
305 - 72 - 34 - 1	12	72	0.134	10	1	10°	.236 x .063	4 CU	37.70	34.56	32.99	31.42
305 - 80 - 22 - 1	12	80	0.087	14	1	5°	.236 x .063	4 CU	26.86	24.62	23.51	22.38
305 - 80 - 24 - 1	12	80	0.094	13	5/8	5°	.236 x .063	4 CU	27.97	25.63	24.47	23.31
305 - 80 - 24 - 2	12	80	0.094	13	1	5°	.236 x .063	4 CU	27.03	24.77	23.66	22.52
305 - 80 - 28 - 1	12	80	0.110	12	1	5°	.236 x .063	4 CU	32.27	29.58	28.23	26.89
305 - 80 - 30 - 1	12	80	0.118	11	1	5°	.236 x .063	4 CU	33.72	30.90	29.50	28.09
305 - 80 - 34 - 1	12	80	0.134	10	1	5°	.236 x .063	4 CU	37.54	34.41	32.84	31.28
305 - 100 - 22 - 1	12	100	0.087	14	1	5°	.236 x .063	4 CU	28.80	26.39	25.20	23.99
305 - 100 - 24 - 1	12	100	0.094	13	1	5°	.236 x .063	4 CU	27.54	25.25	24.09	22.95
305 - 100 - 28 - 1	12	100	0.110	12	1	5°	.236 x .063	4 CU	33.09	30.34	28.96	27.58
305 - 100 - 30 - 1	12	100	0.118	11	1	5°	.236 x .063	4 CU	34.75	31.84	30.41	28.96
305 - 100 - 34 - 1	12	100	0.134	10	1	5°	.236 x .063	4 CU	38.47	35.27	33.65	32.05
355 - 30 - 30 - 1	14	30	0.118	11	1	20°	.252 x .079	4 CU	36.75	33.70	32.15	30.62
355 - 30 - 34 - 1	14	30	0.134	10	1	20°	.252 x .079	4 CU	40.91	37.49	35.79	34.09
355 - 36 - 25 - 1	14	36	0.098	13	1	20°	.252 x .079	4 CU	33.38	30.60	29.21	27.82
355 - 36 - 30 - 1	14	36	0.118	11	1	20°	.252 x .079	4 CU	36.81	33.74	32.21	30.68
355 - 36 - 34 - 1	14	36	0.134	10	1	20°	.252 x .079	4 CU	41.79	38.31	36.57	34.82
355 - 40 - 28 - 1	14	40	0.110	12	1	15°	.236 x .063	4 CU	35.43	32.48	30.99	29.52
355 - 40 - 30 - 1	14	40	0.118	11	1	15°	.236 x .063	4 CU	37.20	34.10	32.55	30.99
355 - 40 - 34 - 10	14	40	0.134	10	1	15°	.236 x .063	4 CU	41.99	38.48	36.73	34.98
355 - 40 - 34 - 2	14	40	0.134	10	2	15°	.236 x .063	4 CU/PH - Diehl	43.71	40.07	38.25	36.42
355 - 60 - 28 - 1	14	60	0.110	12	1	10°	.236 x .063	4 CU	36.79	33.73	32.20	30.66
355 - 60 - 30 - 1	14	60	0.118	11	1	10°	.236 x .063	4 CU	39.18	35.90	34.28	32.65
355 - 60 - 34 - 1	14	60	0.134	10	1	10°	.236 x .063	4 CU	43.62	39.97	38.17	36.35

Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
355 - 72 - 28 - 1	14	72	0.110	12	1	10°	.236 x .063	4 CU	38.39	35.19	33.59	31.99
355 - 72 - 30 - 1	14	72	0.118	11	1	10°	.236 x .063	4 CU	40.30	36.94	35.26	33.58
355 - 72 - 34 - 1	14	72	0.134	10	1	10°	.236 x .063	4 CU	44.88	41.15	39.27	37.41
355 - 80 - 25 - 1	14	80	0.098	13	1	10°	.236 x .063	4 CU	37.61	34.48	32.90	31.34
355 - 80 - 28 - 1	14	80	0.110	12	1	10°	.236 x .063	4 CU	38.71	35.49	33.88	32.27
355 - 80 - 30 - 1	14	80	0.118	11	1	10°	.236 x .063	4 CU	40.32	36.96	35.29	33.60
355 - 80 - 34 - 1	14	80	0.134	10	1	10°	.236 x .063	4 CU	44.60	40.88	39.02	37.16
355 - 100 - 28 - 1	14	100	0.110	12	1	5°	.236 x .063	4 CU	38.67	35.45	33.83	32.22
355 - 100 - 30 - 1	14	100	0.118	11	1	5°	.236 x .063	4 CU	40.30	36.94	35.26	33.58
355 - 100 - 34 - 2	14	100	0.134	10	1	5°	.236 x .063	4 CU	46.30	42.46	40.53	38.59
355 - 120 - 30 - 2	14	120	0.118	11	1	5°	.236 x .063	4 CU	43.04	39.45	37.66	35.87
380 - 100 - 22 - 3	15	100	0.087	14	1	0°	.236 x .063	4 CU	40.50	37.12	35.44	33.75
405 - 24 - 34 - 1	16	24	0.134	10	1	20°	.252 x .079	4 CU	50.58	46.37	44.26	42.15
405 - 30 - 34 - 1	16	30	0.134	10	1	20°	.252 x .079	4 CU	50.86	46.63	44.52	42.39
405 - 36 - 30 - 1	16	36	0.118	11	1	20°	.252 x .079	4 CU	46.66	42.76	40.83	38.87
405 - 36 - 34 - 2	16	36	0.134	10	2	20°	.252 x .079	4 CU/PH - Diehl	53.03	48.60	46.40	44.18
405 - 40 - 28 - 1	16	40	0.110	12	1	15°	.236 x .063	4 CU	43.78	40.12	38.31	36.48
405 - 40 - 30 - 1	16	40	0.118	11	1	15°	.236 x .063	4 CU	43.42	39.81	38.00	36.19
405 - 40 - 34 - 1	16	40	0.134	10	1	15°	.236 x .063	4 CU	47.20	43.26	41.29	39.33
405 - 60 - 28 - 2	16	60	0.110	12	1	10°	.252 x .063	4 CU	44.55	40.84	38.99	37.12
405 - 60 - 30 - 1	16	60	0.118	11	1	10°	.252 x .063	4 CU	46.15	42.30	40.38	38.46
405 - 60 - 34 - 1	16	60	0.134	10	1	10°	.252 x .063	4 CU	49.47	45.36	43.29	41.23
405 - 80 - 30 - 2	16	80	0.118	11	1	10°	.236 x .063	4 CU	46.15	42.30	40.38	38.46
405 - 80 - 34 - 1	16	80	0.134	10	1	10°	.236 x .063	4 CU	49.86	45.71	43.63	41.56
405 - 100 - 30 - 1	16	100	0.118	11	1	5°	.236 x .063	4 CU	47.35	43.40	41.42	39.46
405 - 100 - 34 - 1	16	100	0.134	10	1	5°	.236 x .063	4 CU	50.68	46.45	44.33	42.23
405 - 120 - 30 - 1	16	120	0.118	11	1	5°	.236 x .063	4 CU	46.84	42.95	40.99	39.04
455 - 36 - 34 - 1	18	36	0.134	10	1	20°	.252 x .079	4 CU	59.27	54.31	51.85	49.38
455 - 40 - 34 - 1	18	40	0.134	10	1	15°	.236 x .063	4 CU	60.03	55.02	52.52	50.01
455 - 60 - 34 - 1	18	60	0.134	10	1	10°	.236 x .063	4 CU	62.51	57.30	54.69	52.10
455 - 60 - 38 - 1	18	60	0.150	9	1	10°	.252 x .079	4 CU	76.99	70.58	67.38	64.16
455 - 80 - 34 - 1	18	80	0.134	10	1	10°	.236 x .063	4 CU	64.65	59.27	56.57	53.88
455 - 100 - 34 - 1	18	100	0.134	10	1	10°	.236 x .063	4 CU	65.11	59.69	56.96	54.26
455 - 120 - 34 - 1	18	120	0.134	10	1	5°	.236 x .063	4 CU	66.13	60.62	57.86	55.11



Stock Price List

\$50 Minimum Order

Standard Saws (Rip, Cut-Off, Trim, Etc.) / Saw Bodies for Carbide Tipping

Catalog Number	Diameter (Inches)	Number of Teeth	Thickness		Bore (Inches)	Hook	Seat Pocket (Inches)	Special	Quantities / Price \$US Each			
			.000"	Gauge					1-5	6-20	21-49	50+
505 - 40 - 38 - 1	20	40	0.150	9	1	20°	.252 x .079	4 CU	73.01	66.93	63.88	60.85
505 - 60 - 34 - 1	20	60	0.134	10	1	15°	.252 x .079	4 CU	69.59	63.78	60.88	57.98
505 - 60 - 34 - 3	20	60	0.134	10	1-1/4	0°	.220 x .063	4 CU	69.60	63.80	60.89	58.01
505 - 60 - 38 - 1	20	60	0.150	9	1	15°	.252 x .079	4 CU	75.76	69.45	66.30	63.14
505 - 60 - 38 - 5	20	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	75.76	69.45	66.30	63.14
505 - 80 - 34 - 1	20	80	0.134	10	1	15°	.252 x .079	4 CU	71.71	65.73	62.74	59.75
505 - 80 - 34 - 2	20	80	0.134	10	1-1/4	0°	.220 x .063	4 CU	71.71	65.73	62.74	59.75
505 - 80 - 38 - 1	20	80	0.150	9	1	15°	.252 x .079	4 CU	78.18	71.67	68.41	65.15
505 - 80 - 38 - 11	20	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	78.18	71.67	68.41	65.15
505 - 100 - 34 - 1	20	100	0.134	10	1	10°	.252 x .079	4 CU	74.98	68.72	65.61	62.48
505 - 100 - 34 - 2	20	100	0.134	10	1-1/4	0°	.220 x .063	4 CU	74.98	68.72	65.61	62.48
505 - 100 - 38 - 1	20	100	0.150	9	1	10°	.252 x .079	4 CU	81.22	74.46	71.08	67.69
505 - 100 - 38 - 4	20	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	81.22	74.46	71.08	67.69
505 - 120 - 38 - 1	20	120	0.150	9	1	10°	.252 x .079	4 CU	82.60	75.73	72.28	68.84
560 - 60 - 38 - 1	22	60	0.150	9	1	15°	.252 x .079	4 CU	89.24	81.81	78.09	74.37
560 - 60 - 38 - 10	22	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	89.24	81.81	78.09	74.37
560 - 80 - 38 - 1	22	80	0.150	9	1	15°	.252 x .079	4 CU	91.47	83.86	80.04	76.23
560 - 80 - 38 - 19	22	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	91.47	83.86	80.04	76.23
560 - 100 - 38 - 1	22	100	0.150	9	1	10°	.252 x .079	4 CU	94.97	87.06	83.10	79.14
560 - 100 - 38 - 3	22	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	94.97	87.06	83.10	79.14
560 - 120 - 38 - 1	22	120	0.150	9	1	10°	.252 x .079	5 CU	98.20	90.02	85.92	81.83
610 - 60 - 38 - 1	24	60	0.150	9	1	15°	.252 x .079	4 CU	112.01	102.68	98.01	93.35
610 - 60 - 38 - 7	24	60	0.150	9	1-1/4	0°	.220 x .063	4 CU	112.01	102.68	98.01	93.35
610 - 80 - 38 - 1	24	80	0.150	9	1	15°	.252 x .079	4 CU	115.95	106.28	101.45	96.62
610 - 80 - 38 - 16	24	80	0.150	9	1-1/4	0°	.220 x .063	4 CU	115.95	106.28	101.45	96.62
610 - 100 - 38 - 1	24	100	0.150	9	1	10°	.252 x .079	4 CU	120.92	110.85	105.80	100.77
610 - 100 - 38 - 3	24	100	0.150	9	1-1/4	0°	.220 x .063	4 CU	120.92	110.85	105.80	100.77
660 - 60 - 38 - 1	26	60	0.150	9	1	10°	.252 x .079	4 CU	152.47	139.76	133.41	127.05